



■ 符合标准 / Standard

符合IEC60947-5-1 GB14048.5标准
Conform to IEC60947-5-1 GB14048.5 Standard


■ 触点方式 Contact Style



■ 端子描述 Terminal Description




■ 安装尺寸 / Install Size



■ 连接器 / Connector

快速连接，安全使用，方便连接，
线长可供定制。



■ 开关结构说明 / Switching Operation

型式 Type	符号 Sign	示意图 Diagram	说明 Explanation
No.2			具有两个端子的双断电慢动触头开关个别产品可定制，Y型常闭开关，详见产品说明 Using two terminals, double-break and slow-motion contact. Y type NC switch can be made to order for individual product, pls check the product description.

■ 额定参数/Rating

工作电压 Working voltage			24V	110V	220V
接触参数 Contact Parameter	AC (50/60Hz)	阻性	—	1.0A	0.5A
		感性	—	0.7A	0.5A
	DC	阻性	1.0A	0.2A	—
		感性	0.7A	0.1A	—

J22/25/30/40金属按钮开关 Metal button switch



■ 特性 / Features

- 安装直径22/25/30mm
- 防护等级：IP65/IP67/IK10
- 触点银镀金：3μ
- LED超高亮冷光源灯显示
- 专用特殊磨砂不锈钢环
- 整体美观，高级，时尚



www.otomasyondeposu.com

J22/25/30金属按钮开关命名方式 The naming definition of J22/25/30 metal push button switch

	—						—	
安装尺寸 Install Size		动作方式 Action Style:	头部形状 Shape of Top:	触点形式 Contact Type:	颜色/Color:	电压/Voltage:		材料/Material:
22mm 25mm 30mm 40mm		2:自复按钮 3:自锁按钮 2:Momentary 3:Maintained	1: 平头 2: 高位头 3: 弧面头 6: 高面带灯 7: 平面带灯 8: 点头带灯 A: 弧面带灯 1: Flat Round 2: High Round 3: Domed 6: High Ring Illumated 7: Ring Illumated 8: Dot Illumated A: Domed Illumated	1:1NO+1NC 2:2NO+2NC	 红色 / Red  绿色 / Green  蓝色 / Blue  白色 / White  黄色 / Yellow	D:24VDC E:12VDC F:6.3VDC A1:110VAC A2:220VAC		Ni:不锈钢 T:铜镀镍 G:铜镀铬 Ni:Stainless steel T: Copper Plated Ni G:Copper plated Cr

注: 常规的定制都是不锈钢外壳, 如需铜镀镍外壳, 请在型号后面加T; 如需铜镀铬外壳, 请在型号后面加G

Note: The regular material is Stainless steel, if you want Copper Plated with Ni, please add T behind, if you want Copper Plated Cr, please add G behind.

Ø12
金属按钮

Ø16
金属按钮

Ø19
金属按钮

Ø22
金属按钮

Ø25
金属按钮

Ø30
金属按钮

Ø40
金属按钮

触点规格 Contact Ratings

额定绝缘电压 Rated insulation voltage			250			
发热电流 Heating current Ith			3A温度不超过最大额定值所允许的电流 Temperature does not exceed the maximum allowed current			
额定使用电压 Rated voltage			12V	24V	110V	220V
额定使用电流 Rated current	交流AC 50/60Hz	电阻性负载 Resistive load	—	—	5A	3A
		电感性负载 Inductive load	—	—	3A	2A
	直流DC	电阻性负载 Resistive load	5A	5A	1A	0.5A
		电感性负载 Inductive load	2A	2A	0.2A	0.1A
触点材料Contact material			银镀金Silver Plated Gold			

灯珠规格 Lamp Ratings

灯珠类型Lamp Type	双向LED灯珠(交直流通用) LED lamp(AC/DC)
额定电压Rated Voltage	3V,6V,12V,24V,36V,110V,220VAC/DC
额定电流Rated Current	约15mA 约2mA About 15mA About 2mA
发光颜色LED Color	     
寿命Life	40000小时(参考值) 40000 hours(Reference)
灯珠等效电路 Lamp Circuit diagram	 内置电阻: 采用6V灯珠, 需外接电阻。 采用交直流通用的LED灯珠, 接线端子无正负极区分; 60V以下灯珠已内置保护电阻; Using AC/DC LED lamp, the terminals have no difference of anode and cathode: Using inner resistance for the lamp below 60V. Using 6V lamp when the lamp voltage is above 60V, and need connect outer dropping resistance.

注: 如需单向直流LED灯珠可定做; 其他电压规格可按需求定做。
DC LED and other voltage can be made to order.


Ø30金属防水按钮开关 Metal Waterproof Push Button Switch

名称/外观 Product appearance	带灯形式 Illuminated type	操作类别 Operation	触点 Contact	产品型号 Model	外壳材料 Crust Material
实面圆形 / Flat round 	不带灯 Without LED	自复 Momentary	1NO+1NC	J30-211	Nil:不锈钢 T:铜镀镍 G:铜镀铬 Nil:Stainless steel T: Copper Plated Ni G: Copper plated Cr
			2NO+2NC	J30-212	
		自锁 Maintained	1NO+1NC	J30-311	
			2NO+2NC	J30-312	
高面圆形 / High round 	不带灯 Without LED	自复 Momentary	1NO+1NC	J30-221	
			2NO+2NC	J30-222	
		自锁 Maintained	1NO+1NC	J30-321	
			2NO+2NC	J30-322	
弧面圆形 / Domed round 	不带灯 Without LED	自复 Momentary	1NO+1NC	J30-231	
			2NO+2NC	J30-232	
		自锁 Maintained	1NO+1NC	J30-331	
			2NO+2NC	J30-332	

平钮



单刀/1Pole
双刀/2Pole




L: J30自复 40.6mm
J30自锁 42.25mm

高位钮



单刀/1Pole
双刀/2Pole




L: J30自复 43.15mm
J30自锁 44.8mm

弧钮



单刀/1Pole
双刀/2Pole



L: J30自复 43.15mm
J30自锁 44.8mm

J 系列三色灯金属按钮

带电源符号按钮

金属信号灯

经济型金属按钮

金属按钮

Ø12
金属按钮

Ø16
金属按钮

Ø19
金属按钮

Ø22
金属按钮

Ø25
金属按钮


Ø30
金属按钮

Ø40
金属按钮


Ø30带灯金属防水按钮开关 Metal Waterproof Push Button Switch with LED

名称/外观 Product appearance	带灯形式 Illuminated type	操作类别 Operation	触点 Contact	产品型号 Model	外壳材料 Crust Material	带灯颜色 Color	额定电压 Rated Voltage
高面环形圆形 / High ring round 	带灯 With LED	自复 Momentary	1NO+1NC	J30-261 □●	Nil:不锈钢 T:铜镀镍 G:铜镀铬 Nil:Stainless steel T: Copper Plated Ni G: Copper plated Cr	请用下列颜色编码 替换型号中的"□" R 红色/Red G 绿色/Green Y 黄色/Yellow W 白色/White B 蓝色/Blue	请用下列颜色编码 替换型号中的"●" D:24VDC E:12VDC F:6.3VDC A1:110VAC A2:220VAC
			2NO+2NC	J30-262 □●			
		自锁 Maintained	1NO+1NC	J30-361 □●			
			2NO+2NC	J30-362 □●			
实面环形圆形 / Flat ring round 	带灯 With LED	自复 Momentary	1NO+1NC	J30-271 □●			
			2NO+2NC	J30-272 □●			
		自锁 Maintained	1NO+1NC	J30-371 □●			
			2NO+2NC	J30-372 □●			
实面点头圆形 / High point round 	带灯 With LED	自复 Momentary	1NO+1NC	J30-281 □●			
			2NO+2NC	J30-282 □●			
		自锁 Maintained	1NO+1NC	J30-381 □●			
			2NO+2NC	J30-382 □●			
弧面环形圆形 / Domed ring round 	带灯 With LED	自复 Momentary	1NO+1NC	J30-2A1 □●			
			2NO+2NC	J30-2A2 □●			
		自锁 Maintained	1NO+1NC	J30-3A1 □●			
			2NO+2NC	J30-3A2 □●			


高位钮带灯

单刀/1Pole
双刀/2PoleL: J30自复 43.15mm
J30自锁 44.8mm


平钮带灯

单刀/1Pole
双刀/2PoleL: J30自复 40.6mm
J30自锁 42.25mm

平钮带头灯

单刀/1Pole
双刀/2PoleL: J30自复 40.6mm
J30自锁 42.25mm

弧钮带灯

单刀/1Pole
双刀/2PoleL: J30自复 43.15mm
J30自锁 44.8mm